


QUARTZ INEO ECS



New Low SAPS generation oil especially developed for PEUGEOT AND CITROEN engines. Its very high technology allows fuel savings and optimizes the fonctionnement of the anti-pollution systems, such as the Diesel Particulate Filter.

USES

- TOTAL QUARTZ INEO ECS is a lubricant special Fuel Economy of second generation: it can be used for all Diesel engines (former and new generations). It is also appropriate for the majority of the Gasoline engines (consult the maintenance manual of the vehicle before use).
- TOTAL QUARTZ INEO ECS is essential for the correct fonctionnement of the diesel particulate filter, as for the other systems of postprocessing.
- TOTAL QUARTZ INEO ECS satisfies the most severe cycles of maintenance and in the most difficult conditions of use (motorway, intense urban circulation...), all seasons.

PERFORMANCES

Specifications

ACEA 2007 C2 & A5/B5

OEMS

homologations

QUARTZ INEO ECS is the only low SAPS oil recommended by PEUGEOT and CITROEN.
NORM PSA PEUGEOT & CITROEN B71 2290



CLIENTS BENEFITS

Increased longevity of the particulate filters

- Reinforces the action of the particulate filter and prolongs its lifespan, by avoiding its early filling (50% less of metal components than traditional technology oil).

Fuel savings

- Fuel savings: up to 6 % of fuel savings in starting phase, on average 3.5 % of fuel savings in mixed cycle compared to the use of an ACEA reference oil (tests carried out on a Citroen C4 1.6 HDi).

Respect of the environment

- "ECS_Emission System Control": reduction of the CO2 emissions and the pollutant emissions. In addition to the beneficial effects on the effectiveness of the diesel particulate filter, the fall of the fuel consumption leads to decrease the CO2 emissions, the low rate of phosphorus reinforces the effectiveness of the catalytic pots, EGR valve is less clogged, thus the Nox emissions can be better controlled.

Protection and optimal cleanliness of the engine

- Thanks to immediate lubrication, to the detergent and dispersive additivation which ensures a remarkable cleanliness of the engine, QUARTZ INEO ECS has been developed to follow the most severe cycles of maintenance PSA.

CHARACTERISTICS

TOTAL QUARTZ INEO ECS	Units	SAE grade 5W-30
Sulphated ash content	%	0.69
Phosphorus rate	ppm	800
Sulphur rate	% pds	0.25
Volumetric mass at 15°C	kg/m ³	853,6
Viscosity at 40°C	mm ² /s	63,48
Viscosity at 100°C	mm ² /s	10,60
Viscosity index	-	157
Flash point Cleveland	°C	234
Pour point	°C	-36

The values of the characteristics appearing in this table are typical values given as an indication.

TOTAL LUBRIFIANTS
562, avenue du Parc de l'île
92029 Nanterre Cedex
1/1

QUARTZ INEO ECS
Sheet updated : 01/09
Sticker reference: MPC /01/09



This lubricant used according to our recommendations and for the application for which it is planned does not present a particular risk. A card of data of safety in conformity with the legislation in force in the E.C. is available near your commercial adviser.